

Technical Product Datasheet

Item Code: 5297

HADLEY 50mm C STUDS

Hadley C Studs are cold-rolled steel studs used as part of a Hadley System to create non-loadbearing internal partitions.

Manufactured in accordance with EN 14195:2005










Scan QR code for Hadley System *Golden Thread*Documents: Technical Datasheet, Material Safety
Datasheet, Declaration of Performance (DoP), O&M
Manual and more...

DRY-HAD-XX-ZZ-TE-X-101

Rev	Date	Comment	Ву	Chk	Арр
1.0	19/08/24	First Issue	FM	SH	JS
2.0	07/11/24	Second Issue	FM	SH	JS

Width	50mm		
Flange	32mm/34mm		
Gauge	0.50mm		
Lengths	2.4m / 2.7m / 3.0m / 3.6m / 4.2m		

Product Information



REACTION TO FIRE:

Α1

YIELD STRENGTH:

210 (N/mm2)

SERVICE CUT OUTS:

80mm x 30mm @ 600mm Centres

SYSTEM PERFORMANCE INFORMATION:

To be installed as a part of a complete Hadley system to achieve both Fire and Acoustic performance. To understand more about our fully warranted and tested solutions, please contact our Hadley Construction Technology Team.

STORAGE & HANDLING:

Pack Quantities

When installing Hadley components please ensure full PPE is used and the site is practicing a safe working environment alongside industry standards.

10 / 50 / 300

DISPOSAL:

Hadley Metal is fully recyclable.

SYSTEMS USED:

HadleySOLO - Single Stud System

HadleyDUO – Twin Frame I Stud System (*used only at abutments)

HadleyBRACE - Braced Twin Frame System

HadleyHUSH – Single Stud System using Resilient Bars

HadleySTAGGER – Staggered Stud System (*used only at abutments)

HadleyLINE- Independent I Stud Lining System (*used only at abutments)